



Feigete Intelligent Technology Co.,Limited

ADD: 2 Floor,Building No.51,Bantian No.3 Industrial Area,Longgang District,Shenzhen

TEL:86-755-82338710

website: www.smartfeigete.com

Model NO.

KMP-III Portable Thermal Printer



Print Method		Thermalprinting
Resolution		203dpi(8dots/mm)
Print speed		Max:50mm/ss
Print width		72mm
Paper Width		80±0.5mm
Diameter		Max:50mm
InnerDiameter	Min:13mm	
Paper Thickness	0.06-0.09mm	
Dimension (W*D*H)	99*127*55.5mm	
PrintFont	ANK:9X17,9x24,16x18,12x24GBK:24x24	
Character Per Line	ANK:48,42,32 GBK:24,16	
TPH	> 50km(12.5%printratioorless)	
Barcode	1D) -A,UPC-E,EAN-13,EAN8,CODE39,CODE93, CODE128,CODEBAR,ITF25	
	2D) QR CODE	
Interface	Type-CUSB+Bluetooth	
Battery	2000mAh 7.4V	
Recharge adapter	DC12V/1Aor5V/1AUSB charging	
Cutter type	Tear-Bar	
Command	Compatible with ESC/POS command set	
Detection	No paper detection; Photoelectricdetection	
Operating Temperature	0°C~50°C	
OperatingHumidity	20%~85%RH	
Charging Temperature	5°C~40°C	
Charging Humidity	20%~85%RH	
StorageTemperature	-20°C~60°C	
Storage Humidity	5%~90%RH	